




	HS2X <i>HyperFire 2 Security Covert IR Camera</i>	HF2X <i>HyperFire 2 Covert IR Camera</i>	HP2X <i>HyperFire 2 Professional Covert IR Camera</i>
			
	\$459.99 Add to Cart	\$399.99 Add to Cart	\$459.99 Add to Cart
Primary Application	Security surveillance applications	Covert Scouting	Wildlife Research
Image Resolution	1080P HD Wide Screen or 3 Mega-pixel Standard Aspect Ratio	1080P HD Wide Screen or 3 Mega-pixel Standard Aspect Ratio	1080P HD Wide Screen or 3 Mega-pixel Standard Aspect Ratio
Video	720P HD Video with Audio	720P HD Video with Audio	720P HD Video with Audio
Video Length	Up to 90 Seconds	Up to 10 Seconds	Up to 90 Seconds
Product Warranty	5 years	5 years	5 years
Dimensions	5.5"H x 4.5"W x 2.5"D	5.5"H x 4.5"W x 2.5"D	5.5"H x 4.5"W x 2.5"D
Operating Temperature	-20° to +120° Fahrenheit	-20° to +120° Fahrenheit	-40° to +140° Fahrenheit
Illumination	No-Glow™ High Output Covert IR	No-Glow™ High Output Covert IR	No-Glow™ High Output Covert IR
Illumination Range	Up to 150 feet	Up to 150 feet	Up to 150 feet
Illumination On/Off Option	✓	✓	✓
Illumination Power Settings	Low/Med/High	Low/Med/High	Low
Mapping & Image Management Software	SecurityView™ Image Management & Configuration Software	BuckView™ Advanced	MapView™ Professional & Configuration Software
User Defined Metadata in MapView™	✓	n/a	✓
Metadata Export from MapView™	Y	n/a	✓
Image Detail	Color by Day, Monochrome Infrared by Night	Color by Day, Monochrome Infrared by Night	Color by Day, Monochrome Infrared by Night
Trigger Speed	0.2 second	0.2 second	0.2 second
PIR Detect Range	Up to 100ft	Up to 100ft	Up to 100ft
RapidFire™ Near-Video Speed	Up to 2 frames per second	Up to 2 frames per second	Up to 2 frames per second
Frame Rate	RapidFire™ to 10 seconds between images	RapidFire to 10 seconds between images	RapidFire™ to 10 sec, 15 sec, 30 sec, 45 sec, 1 min between images
Photos per Trigger	1 to 10 images per trigger	1 to 10 images per trigger	1 to 90 images per trigger
Delay After Triggering	0.5,10,15,30 sec, 1,2,3,5 min	0.5,10,15,30 sec, 1,2,3,5 min	0.5,10,15,30 sec, 1,2,3,5,10,15,30,45 min, 1 hour
Delayed Start up to 1 Year	n/a	n/a	Y
Day/Night Options for Pics and Videos	Y	Y	Y
Night Time Shutter Speed	1/30 or 1/60 (fast shutter)	1/30 or 1/60 (fast shutter)	1/30, 1/60, 1/120, 1/240, 1/480
Max ISO Setting	1600 or 3200 (longe range)	1600 or 3200 (longe range)	800, 1600, 3200
Motion Sensor Scheduling	ON or OFF and Scheduled operation by day	ON or OFF (no scheduling)	ON or OFF and Scheduled operation by day
Time-Lapse Scheduling	Up to 5 start and stop times (fixed and solar)	Up to 2 start and stop times (fixed and solar)	Up to 5 start and stop times (fixed and solar)
Day of the Week Scheduling for Time Lapse	Y	n/a	Y
Loop Recording	✓	n/a	Y
Memory Card Type	Secure Digital (SD®, SDHC® or SDXC®)	Secure Digital (SD®, SDHC® or SDXC®)	Secure Digital (SD® or SDHC®, SDXC®)
Memory Card Capacity	Up to 512GB	Up to 512GB	Up to 512GB
Image Data	Time, Date, Temperature, User Label, Moon Phase	Time, Date, Temperature, User Label and Moon Phase	Time, Date, Temperature, User Label and Moon Phase
Geo-Tagging of Pictures	Y	Y	Y
Battery Life	Up to 40,000 images or 2 years	Up to 40,000 images or 2 years	Up to 40,000 images or 2 years
Battery Requirements	NiMH Rechargeable or 1.5volt Lithium only	NiMH Rechargeable or Energizer Ultimate Lithium	NiMH Rechargeable or Energizer Ultimate Lithium
Battery Quantity / Size	12 AA	12 AA	12 AA
External Power Connection	Optional	n/a	Optional
Camera Settings	Available options are set on camera	Available options are set on camera	Available options are set on Camera or with the included Software
Camera Settings Export	n/a	n/a	Y
Customization	n/a	n/a	Custom Focus, External Power, External Trigger
Theft Deterrence	CodeLoc™ Pass-Code Protection	CodeLoc™ Pass-Code Protection	CodeLoc™ Pass-Code Protection

[Show Fewer Features](#)